

Название компании: Разработано: Телефон:

Дата: 9/18/2025

Счет | Параметр

1 | COMFORT 15-14 BX



Внимание! Фотография продукта может отличаться от существующего.

Номер изделия: 97916772

COMFORT is an efficient circulator designed for hot-water recirculation in residential buildings with a dedicated return line. It is compatible with all types of water heater tanks, tankless systems, solar or heat pumps whether or not the system has mixing or tampering valves installed.

The pump features a compact housing and a permanent magnet with an integrated control unit. The spherical rotor, equipped with an impeller, ensures optimal functionality supported by a robust single-bearing ball system. The drinking-water approved brass pump housing guarantees both safety and reliability.

COMFORT features the continuous operation 24/7 mode which is suitable for external control via plug-in timer, gas boiler or heat-pump controller.

The product features:

- Q-H performance that is designed for single- and multi-family homes, depending on the required duty point to accommodate heat loss in a specific pipe layout.
- · Low power consumption and silent operation.
- · Compliance with pipe manufacturers' flow velocity limits, including DN 15, DN 20 PEX, copper and others.
- Drinking-water approved thanks to the brass pump housing, stainless-steel rotor and composite impeller.
- A design that makes it easy to remove limescale and foreign deposits by removing the pump head, enabling
 the product to meet unlimited water hardness requirements.
- Dry-running protection to prevent failure if the system runs out of water.
- Multiple installation positions, even with the pump head pointing downwards.
- A pump head designed to fit brass pump housings of old and new pumps of the same design, even from different pump manufacturers (such as Wilo, Vortex, Lowara, DAB and others).
- Easy electrical installation with a pre-assembled power plug with a 1.5 m cable and a double insulation protection design, which eliminates the need for a ground wire.
- · Insulating shells for heat loss reduction.
- Non-return and shut-off valves included in ""BX"" variant, reducing installation cost.
- An optional venting flange that provides a simple way to vent or drain the system without the need to install an additional permanent venting valve.
- · Optional fittings for pipe connections of different sizes and types.
- Optional non-return and shut-off valves are available.



Название компании: Разработано: Телефон:

Дата:	9/18/202
Haia.	0/10/20/

Описание	Значение
Общие сведения:	
Наименование продукта:	COMFORT 15-14 BX
№ продукта:	97916772
EAN код:	5710626363773
Технические данные:	
Количество скоростей:	1
Номинальный расход:	0.33 м³/ч
Номинальный напор:	0.78 м
Максимальный напор:	14 дм
ТЕ класс:	95
Сертификаты:	CE,VDE,EAC,WEEE
Материалы:	
Корпус насоса:	Brass
Материал корпуса насоса:	CuZn39Pb3, MS58
Рабочее колесо:	Composite
	PPO-GF20/Stainless steel
Монтаж:	
Minimum ambient temperature:	0 °C
Макс. рабочее давление:	10 бар
Pipe connection standard:	ISO 228-1
Стандарт трубного присоединения:	G
Диаметр обсадной колонны:	1 inch
Допустимое давление:	PN 10
Монтажная длина:	140 мм
Жидкость:	
Рабочая жидкость:	Вода
Диапазон температур жидкости:	2 95 °C
Температура перекачиваемой жидкости:	60 °C
Плотность:	983.2 кг/м³
Данные электрооборудования:	
Макс. потребляемая мощность:	7 Вт
Частота питающей сети:	50 / 60 Hz
Номин.напряжение:	1 x 230 B
Ток при скорости 3:	0.07 A
Степень защиты (IEC 34-5):	IP44
Класс изоляции (IEC 85):	F
Стандарт. Ех-защиты:	ELECT.
Тепловая защита:	Impedance protected
Система управления:	· · · · · · · · · · · · · · · · · · ·
Operation mode include:	None
Другое:	
Вес(Нетто):	1.14 кг
Вес(Брутто):	1.24 кг
Объем поставки:	0.003 M ³
Danish VVS No.:	380635110
Swedish RSK No.:	5803086
Norwegian NRF no.:	9042116
INOTINGUIAITININ 110	3042110



